



DRAFT INTERNATIONAL STANDARD ISO/DIS 22096

ISO/TC 108/SC 5

Secretariat: ANSI

Voting begins on:
2006-03-28

Voting terminates on:
2006-08-28

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Condition monitoring and diagnostics of machines — Acoustic emission

Surveillance et diagnostic d'état des machines — Émission acoustique

ICS 17.160

In accordance with the provisions of Council Resolution 15/1993 this document is circulated in the English language only.

Conformément aux dispositions de la Résolution du Conseil 15/1993, ce document est distribué en version anglaise seulement.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols and abbreviated terms	3
5 Principle of the acoustic emission technology	3
5.1 The acoustic emission (AE) phenomenon	3
5.2 Advantages and limitations of acoustic emission	3
6 Applications of the acoustic emission technique	3
6.1 Machinery monitored by acoustic emission	3
6.2 Interference factors.....	5
7 Data acquisition	5
7.1 Installing a system	5
7.2 AE instrumentation and sensors	5
7.3 Sensor installation and coupling media for structure-borne monitoring	5
8 Preliminary information.....	6
9 Data analysis and presentation of results	7
10 Establishing procedures	7
Bibliography.....	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22096 was prepared by Technical Committee ISO/TC 108, *Mechanical vibration and shock*, Subcommittee SC 5, *Condition monitoring and diagnostics of machines*.

Introduction

Acoustic Emission (AE) technology can be used as a stand-alone condition monitoring technique that may also be employed to complement other condition monitoring techniques based on other technologies (e.g. vibration, infrared, etc.) used for machine condition analysis and diagnosis/prognosis. Due to the nature of AE, an understanding of the operating mechanics of the monitored machine is not essential, but such an understanding allows the maximum amount of data to be extracted from the results of the AE phenomena. As a diagnostic tool for machine condition monitoring, AE can be employed as a permanently installed, semi-permanent or portable system, depending on the criticality of the machine. Typically, an AE system would contain transducers, amplifiers, filters and data acquisition systems. Depending on the particular application, a range of data can be extracted from the capture AE to provide indicators for machine condition.

Condition monitoring and diagnostics of machines — Acoustic emission

1 Scope

This International Standard specifies the general principles required for the application of Acoustic Emission (AE) to condition monitoring and diagnostics of machinery operating under a range of conditions and environments. It is applicable to all machinery and associated components and covers structure-borne measurements only.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Vibration and Shock — Vocabulary*

ISO 17359, *Condition monitoring and diagnostics of machines — General guidelines*

ISO 13372, *Condition monitoring and diagnostics of machines — Vocabulary*

EN 1330:9, *Non-destructive testing — Acoustic emission — Terms used in acoustic emission testing*

3 Terms and definitions

For the purposes of this International Standard, the terms and definitions given in ISO 2041, ISO 13372, EN 1330:9 and the following apply.

3.1

acoustic emission

range of phenomena that results in structure-borne and fluid-borne (liquid, gas) propagating waves being generated by the rapid release of energy from localised sources within and/or, on the surface of a material

NOTE 1 Such release may be a result of a process such as crack propagation, friction, impact, leakage, etc.

NOTE 2 The definition of acoustic emission in this document conveys its broad application in machine monitoring.

3.2

acoustic emission monitoring

detection and collection of information and acoustic emission data that indicate the state of a machine

NOTE The definition of acoustic emission monitoring in this document relates to the application in machine monitoring.

3.3

acoustic emission sensor/receiver

device containing a transducing element that converts elastic wave motion into an electrical signal

3.4

acoustic emission signal

electrical signal from an acoustic emission sensor

3.5

acoustic emission characteristics

set of specific characteristics describing acoustic emission associated with a machine or an acoustic emission source

NOTE The signature can be of a burst type, i.e. emission events which can be separated in time; or a continuous type, i.e. emissions which cannot be separated in time.

3.6

acoustic emission waveguide

device which allows the transfer of elastic waves from the machine to an acoustic emission sensor

3.7

background noise

false signals produced by causes other than acoustic emission or by acoustic emission sources that are not relevant to the machine component being monitored

NOTE This can include electrical, thermal and mechanical origins.

3.8

couplant

coupling media between AE sensor and the object from which measurement is to be acquired

EXAMPLES Soil, grease, adhesive bond, water soluble paste, wax.

3.9

Hsu-Nielsen source

pencil lead break device to simulate an acoustic emission event using the fracture of a brittle graphite lead in a suitable fitting

NOTE Changes in signal can be due to variations in the lead. Typically lead 2H Diameter 0.5mm (alternatively 0.3mm), length 3.0 ± 0.5 mm, is employed.

3.10

machine

mechanical system designed expressly to perform a specific task, such as the forming of material or the transference and transformation of motion, force or energy

NOTE This is also sometimes referred to as equipment.

3.11

machine system

machine train (deprecated)

mechanical system in which the principal subsystem is a specific machine (3.11) and whose other subsystems are components and auxiliaries whose individual functions are integrated to support the actions and work of the machine

4 Symbols and abbreviated terms

AE Acoustic emission

5 Principle of the acoustic emission technology

5.1 The acoustic emission (AE) phenomenon

Acoustic emission is a physical phenomenon occurring within and/or on the surface of materials. The term acoustic emission is used to describe the spontaneous elastic energy released by a process in the form of transient elastic waves. Acoustic emissions generated within a material manifest as elastic waves on the surface of the material and cover a broad frequency range. Typically the frequency content of detected acoustic emission signals fall within the range of 20 kHz to 1MHz.

The waves associated with AE are detected by the use of a suitable sensor that converts the surface displacement of the material into an electric signal. These electric signals are processed by appropriate instrumentation and/or data processing techniques, to characterise the system condition and aid in detection of the early stages of loss of mechanical and structural integrity. The signal waveform from the sensor is affected by multiple path propagation and several wave modes that are generated in and/or on the material. As such the sensor response for identical input sources that propagate through varying transmissions paths will be different.

5.2 Advantages and limitations of acoustic emission

AE offers the following advantages:

- it is non invasive;
- provides real time process information;
- may offer earlier fault detection than vibration analysis due to its higher sensitivity;
- it offers monitoring of dynamic performance;
- it can be applied to a wide range of rotational speeds with significant advantages at slow rotational speeds [in the order of less than 1 Hz (60 r/min)];
- it allows for detection of the friction/wear process, for instance, rubbing between loose mating components or deterioration in lubricating condition.

Limitations of AE include:

- susceptibility to attenuation;
- susceptibility to high operational background noise;
- inability to relate the resultant defect AE signature to the exact fault mechanism.

6 Applications of the acoustic emission technique

6.1 Machinery monitored by acoustic emission

The acoustic emission technology can be applied to a wide range of machinery provided a transmission path from the position of the sensor to the region of interest exists. This is particularly important for structure-borne AE monitoring; some examples are detailed in Table 1. The method does not rely on absolute quantities of

measured AE parameters but on trends of AE parameters that are measured during a specified operational condition. For instance, an increasing trend in the detected AE signal level under steady operating conditions is indicative of machine deterioration. For example, AE signal amplitude modulated at a bearing defect frequency is indicative of early stages of bearing element defect, which may not be detectable with vibration or shock pulse monitoring. It must be noted that AE activity will vary for differing machines, operating conditions and machine loading.

Table 1 – Examples of applications of AE to machine condition monitoring

Machine type	Fault						
	Bearing deterioration	Mechanical seal rubbing	Wear	Lubricant contamination and loss of lubricant	Severe misalignment	Mounting faults	Process monitoring including leakage, performance, etc
Pump	•	•	•	•	•	•	•
Gear box	•		•	•	•	•	•
Electric motor	•			•	•	•	
Steam turbine	•	•		•	•	•	•
Industrial gas turbine	•	•		•	•	•	•
Electric generator	•			•		•	
Diesel Engine			•				•
Machining processes	•		•	•			
Fan or Blower	•			•	•		•
Slow speed rotating machine (typically <60 rev/min)	•			•	•	•	•
Machine components e.g. valves, heat exchangers, etc			•	•		•	•
Compressors (air, gas, etc)	•	•	•	•	•	•	•

6.2 Interference factors

Prior to performing an AE measurement, it is very important to be aware of potential noise sources, such as electronic noise (electromagnetic and radio frequency interference), airborne noise (such as gas leaks, the impact of sand particles on the machine in windy environments), operational background noise (flow of fluids in pipes) and mechanical background noise whose presence might affect the AE measurement.

7 Data acquisition

7.1 Installing a system

A schematic diagram of a typical structure-borne AE data acquisition system is illustrated in Figure 1. Typically the sensor is coupled to the machine under observation. This in turn is usually connected to a pre-amplifier, which is connected to an acquisition system. Some AE sensors have built in pre-amplifiers. The data shall be acquired while the machine is operational and the amount of data acquired and extent of analysis depends upon the particular application. The system can be permanent, semi-permanent or portable. For airborne acquisition the AE receiver/sensor may be scanned over the region of interest.




Figure 1 – Schematic diagram of an acquisition system

7.2 AE instrumentation and sensors

Detection is the most important part of an AE chain and every attempt should be undertaken to overcome poor installation and acoustical coupling. Furthermore, the effects of incorrect frequency selection for filters, sensors, acquisition rates, etc, should be considered. Sensor parameters that shall be considered include size, sensitivity, frequency response and environment. In addition, for airborne AE acquisition the influence of humidity should also be considered.

7.3 Sensor installation and coupling media for structure-borne monitoring

For structure-borne monitoring the purpose of the mounting arrangement is to ensure the sensor is fixed onto a structure with an adequate coupling media (couplant). Mounting methods will be either with a mechanical arrangement (compression force applied with a magnet, mechanical clamp, etc) or with an adhesive. In the latter instance, the adhesive also serves as the couplant.

The location of the AE sensor should ensure a transmission path to the machine component under observation. This path can include surface discontinuities (a discontinuity is defined as an interface, for instance, the interface between a bolt head and the clamped component), however, these surfaces should be in contact either directly or across a couplant (for example, a transmission path across a plain journal bearing where the lubricating and cooling oil serves as the couplant for transmission). In addition, the surface onto which the sensor is placed shall be clean. The signal transmission path can be improved by removing any surface paint to expose the metal substrate; however removal of any coat should not degrade the machine integrity or performance. Every attempt shall be made to ensure the surface of the sensor is fixed flat onto the surface, avoiding surface curvature, contaminating particles or surface discontinuities. The primary purpose of this procedure is to improve transmission paths and ensure repeatability.

Under certain conditions the AE sensor can be installed on a waveguide. Usually the waveguide is constructed to ensure a more direct transmission path between the sensor and machine component under

observation and/or effect a reduction in the temperature experienced by the AE sensor. The waveguide can affect the acquired AE wave, for instance, attenuation, waveform shape, etc.

The couplant can be applied by placing a small amount in the centre of the intended position of the sensor, which is then carefully pressed onto the surface, spreading the couplant uniformly. The thickness of the couplant can alter the sensitivity of the sensor.

In conditions where the use of a couplant is impractical a dry contact may be used. In this case, the necessary contact pressure shall be determined experimentally, for instance, with the Hsu-Nielsen source. Attempts should be made to ensure air or voids are not present between the sensor front face and the surface of the machine,

When an adhesive couplant is used, ensure that the bond employed to fix the AE sensors to a structure does not break or peel off as a direct result of surface deformation, thermal expansion or mechanical loading. Also ensure that the characteristics of the adhesive with respect to the operating conditions and environment are known.

NOTE Bond cracking can be a source of Acoustic Emission.

It is important to isolate the sensor electrically to prevent background noise encroaching through the electrical ground.

8 Preliminary information

The preparation and the execution of the examination as well as interpretation of the results necessitate prior knowledge of:

- identification name and number of machine;
- detail of current operating conditions (load, speed, temperature, etc.);
- history of service and maintenance actions;
- mechanical design details;
- history of previous operating conditions;
- any previous AE data.

Interpretation of results shall require reference to a relevant experimental database or operational condition of known mechanical integrity; a baseline. A baseline is data or sets of data as measured or observed when the equipment operation is known to be acceptable and stable. Subsequent measurements can be compared to these baseline values to detect changes. Baseline data should accurately define the initial stable condition of the machine, preferably operating in its normal operating state.

For machines with several operational states, it may be necessary to establish baselines for each of these states. For new and overhauled equipment there may be a wear-in period. As a result, it is common to see a change in measured values during the first few days or weeks of operation. Therefore, time should be allotted for wear-in before acquiring baseline data. For equipment which has been operating for a significant period, and monitored for the first time, a baseline can still be established as a trending reference point.

9 Data analysis and presentation of results

The primary purpose of data analysis is to relate AE activity to operating condition; measuring or monitoring any deviation from baseline conditions assist in identifying the condition of the machine.

Examples of criteria adopted for AE evaluation of machinery condition are:

- AE activity that consistently increases with increasing time;
- The magnitude of AE activity during periods of steady state operation;
- Appearance of signal features not present when running the machine in good condition;
- Instrument-specific methods based on proprietary signal characterisation built into a manufacturer's instrument;
- Presence of signal amplitude modulations at defect repetition frequencies;

10 Establishing procedures

It must be emphasised that obtaining successful AE measurements is based on repetitive accurate monitoring within set parameters. This requires AE personnel to be competent at establishing, verifying and/or implementing documented procedures for the application of specific types of tests, with an understanding of their limitations. These competency requirements are specified in ISO 18436-6.

Bibliography

- [1] EN 13554, *Non-destructive testing — Acoustic emission — General principles*
- [2] DSTU 4227, *Guidelines on acoustic-emission diagnostics of critical objects*
- [3] ASTM E976, *Standard Guide for Determining the Reproducibility of Acoustic Emission Sensor Response*
- [4] ISO 18436-6, *Condition monitoring and diagnostics of machines- Requirements for training and certification of personnel: Part 6: Acoustic Emission*